

This is Why

- ▶ 47" (119,3 CM) DISPLAY FOR PROFESSIONAL 24/7 SIGNAGE
- ▶ 1920 X 1080 PIXELS WITH 700CD/M2
- ▶ BUILT-IN STEREO SPEAKERS 10 + 10W AND UV2A LCD TECHNOLOGY
- ▶ BRIGHTNESS 700CD/M2
- ▶ LED, EDGE LIT
- ▶ 24 / 7 OPERATION
- ▶ HDMI AND DISPLAYPORT
- ▶ LANDSCAPE & PORTRAIT INSTALLATION SUPPORT



Built for 24/7 durability, and sized for flexible installation, the PN-U473 represents a dynamic new breed of indoor digital signage solutions. Thin and lightweight enough for easy installation in stores, offices, and public spaces, this monitor boasts the outstanding image quality (700 cd/m2) needed to deliver truly compelling digital signage.

DISPLAY MODULE DATA

- ▶ Panel Technology: **LCD UV2A**
- ▶ Native Resolution (Pixels): **1920 X 1080**
- ▶ Diagonal Size (inches / cm): **47/119.3**
- ▶ Aspect Ratio: **16:9**
- ▶ Backlight Technology: **EDGE LED**
- ▶ Brightness (cd/m2): **700**
- ▶ Contrast Ratio: **1300:1**
- ▶ Display Colours: **1.06b**
- ▶ Response Time (grey to grey avg) ms: **12**
- ▶ Viewing Angle (H/V) 0 CR >10: **178/178**

POWER SUPPLY AND OPERATING ENVIRONMENT

- ▶ Operating Voltage(ACV) / Frequency(Hz): **100 - 240/50 - 60**
- ▶ Power Consumption (W) (Operating MAX): **130**
- ▶ Power Consumption (W) (Standby): **0.5**
- ▶ Operating Temperature (oC): **0 - 40**
- ▶ Humidity (%): **20 - 80**
- ▶ Heat Dissipation (BTU/h) MAX: **443.58**

WEIGHTS AND MEASURES

- ▶ Bezel Size (L/R) mm: **20**
- ▶ Bezel Size (U/L) mm: **19**
- ▶ Product Dimensions (W/H/D) mm: **1083 X 627 X 55**
- ▶ Product Weight Without Stand (Kg): **19**

CONNECTIVITY (AUDIO/VIDEO) INPUT

- ▶ HDMI: **1**
- ▶ DVI-D: **1**
- ▶ DisplayPort: **1**
- ▶ Component: **1**
- ▶ Composite: **1**
- ▶ Audio 3.5mm Jack: **1**

CONNECTIVITY (CONTROL/SERIAL DATA)

- ▶ RS232C IN: **1**
- ▶ RS232C OUT: **1**
- ▶ LAN Port: **1**

KEY SPECIFICATIONS

- ▶ 24/7 Operation Certified: ✓
- ▶ Built in Speakers (W): **10 X 10**
- ▶ Computer Input - Plug and Play: ✓
- ▶ Power Management: ✓
- ▶ Cabinet Colour: **BLACK**
- ▶ Fanless: ✓
- ▶ Multi-Screen Function - Videowall Mode (Enlarge Feature): ✓
- ▶ Daisychain (Mirror mode): ✓
- ▶ Hardware Diagnosis: ✓
- ▶ Monitor Control Software Support: ✓

SAFETY AND ENVIRONMENT (EUROPE)

- ▶ CE, CB Report: ✓
- ▶ Mercury Content (mg): **0**
- ▶ Presence of Lead (Accepted application of RoHS Directive): ✓

INSTALLATION

- ▶ Landscape: ✓
- ▶ Portrait: ✓
- ▶ Mounting (VESA/Number of Points/Pitch mm): **4/400mm x 200mm**

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

- ▶ DVI-D: **1**
- ▶ Audio RCA R-L: **1**

www.sharp-cee.com

SHARP

HEADQUARTERS SHARP CENTRAL & EASTERN EUROPE
A-1020 VIENNA
HANDELSKAI 342
AUSTRIA
PHONE: +43 1 72719-0
FAX: +43 1 72719-289
INTERNET: WWW.SHARP-CEE.COM