

Monitory biurkowe

# SHARP/ NEC MULTISYNC EA271F



## NEC MultiSync

- Ergonomic Office – full height adjustability (150 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.
- Protecting your eyes from strain and damage – Built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.
- Ease of multi-display control – manage the settings of up to 5 displays in a multi-monitor configuration via the master display with ControlSync® technology.
- Maximise image quality with Uniformity Control – benefit from perfect uniformity across multi-screen setups with just one click in the display's on-screen menu.

# Dane techniczne

Technologia panelu	AH-IPS LCD with LED backlight
Proporcje obrazu	16:9
Jasność (cd/m <sup>2</sup> )	250
Współczynnik kontrastu	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
Wyświetlane kolory	16.78
Czas odpowiedzi (szary-do-szarego, średni) ms	6
Wymiary piksela (mm, w poziomie/w pionie)	0,311
Energy Efficiency	Ambient light sensor, Auto brightness, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 11 kWh/1000 h, Energy efficiency class: C, Human sensor, LED backlight technology
Ecological Standards	Efficient mechanical design for minimised packaging, Minimal use of harmful material
Ecological Materials	Energy Star 8.0, ErP compliant, TCO 8.0, WEEE
Special Characteristics	ControlSync®, Carbon Savings Meter, DICOM preset, Customize Setting, DDC/CI compatible, RGB Support, Frame Comp, ErgoDesign®, LED Backlight Technology, Picture-by-Picture, PLink Support, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Touch Sensor Keys, USB ver. 3.0 (3 down / 1 up), Flicker Free
Optimum Resolution	1920 x 1080 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 720 x 400 (70 Hz), 800 x 600
Temperatura podczas pracy (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
Przekątna (cale/cm)	27
Przekątna (cale/cm)	69
Colour Gamuts	102 % sRGB, 75.5% AdobeRGB, 72% NTSC
Digital	DisplayPort, DVI-D, HDMI, USB ver. 3.1 (3 down / 1 up)
Analog	VGA
System montażu (VESA/liczba punktów/rozstaw w mm)	100 x 100
Gniazdo zabezpieczające	True

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	DDC2B/2Bi, EDID Standard, VESA DDC/CI
Audio	Sluchawkowe, Integrated Speakers (1 W + 1 W)
Adjust Functions	Audio Volume / Lock-Out, Auto Adjust, Jasność, Colour Temperature Control, Kontrastu, Control Sync, DV Mode, EcoMode, Factory Preset, Fine Adjust (analog), Human Sensing, Intelligent Power Management, Language Select, Monitor Information, NTAA (Non-Touch-Auto-Adjustment), On-Screen-Display (OSD) lock-out, One Touch Recovery, Power-Off Timer, sRGB CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class 2), ISO 9241-307 (pixel failure class 1), Low Blue Light, PSB, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Safety & Ergonomics	3 years warranty incl. backlight, Optional 1st to 3rd year 24/7 usage warranty, Optional 4th to 5th year warranty extension
Gwarancja producenta (lata)	MDSVSENSOR Value
Optional Accessories	
Height adjustable stand [mm]	150
Screen Swivel [°]	-170 - Value
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	360
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	628
[AVSpecificationPortraitDimensionsHeightMaxMm]	653
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
<b>Wyposażenie</b>	
Shipping Content	Control Sync cable, DisplayPort Cable, Monitor, Power Cable, Setup Manual, Setup Guide, USB cable
Pobór mocy w trybie pracy (IEC62087:2012)	12 (Eco Mode 2), 17 (Eco Mode), 17 (typ.), 45 (max.)
Power Supply	0.85 A/0.45 A, 100-240 V, Integrated Power Supply
Masa produktu bez podstawy (kg)	5
Masa produktu z podstawą (kg)	8
Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	50 - 75

Operating Humidity (min) [%] 20  
Operating Humidity (max) [%] 80

Wymiary ramki (lewa/prawa) mm 1  
Wymiary ramki (górn) mm 1



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett\_x0002\_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp/ NEC MultiSync EA271F, 23/6/2026