

Projektor

# SHARP/ NEC P554U PROJECTOR



- Professional and Flexible Installation – versatile projection characteristics allow for simple positioning of the projector, making installation easy and potentially saving set up costs.
- High brightness – for best performance in bright ambient light.
- Cost Saving Device Management – save effort whilst administrating all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.
- Minimized cost of ownership – due to long lamp life and filter exchange intervals.
- Cost effective replacement – of existing NEC P model installations to achieve better imaging for lectures and presentations without wall-mount adjustment.

# Dane techniczne

[AVSpecificationDataTerminalsIn]	HDMI, 15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr)
[AVSpecificationVideoColourStandards]	PAL 60, PAL N, PAL M, SECAM, NTSC (MHz) 3.58, NTSC (MHz) 4.44
<b>Wyposażenie</b>	
[AVSpecificationAccessories]	Pilot zdalnego sterowania, Instrukcja obsługi (CD-ROM), Kabel zasilający
[AVSpecificationVideoTerminals]	S-Video (Y/C), HDMI
[AVSpecificationControlTerminals]	RS232C, LAN, USB-Host

[AVSpecification3LcdPanel]	True
[AVSpecificationWeightKg]	4,8
[AVSpecificationLuminanceEcoModeAnsiLumen]	3200
[AVSpecificationLuminanceStandardAnsiLumen]	5300
[AVSpecificationProjectionLampW]	330
[AVSpecificationLampLifetimeEcoModeH]	8000
[AVSpecificationLampLifeStandardH]	4000
[AVSpecificationFanEcoDb]	34
[AVSpecificationFanStandardDb]	37
[AVSpecificationChangeableLens]	True
[AVSpecificationZoomLensManual]	True
[AVSpecificationLensShiftH]	True
[AVSpecificationLensShiftV]	True
[AVSpecificationKeystoneManual]	True
[AVSpecificationHFrequencekhz]	15 - 100
[AVSpecificationVFrequenceHz]	50 - 120
[AVSpecificationAudioTerminals]	Mini Jack (3,5 mm) wej./wyj., Gniazda RCA wej./wyj.

Rozdzielczość znamionowa (piksele)	1920 x 1200 (WUXGA)
Współczynnik kontrastu	20000:1

