

# This is Why



- ▶ 47" (119,3 CM) DISPLAY FOR PROFESSIONAL 24/7 SIGNAGE
- ▶ 1920 X 1080 PIXELS WITH 700CD/M2
- ▶ BUILT-IN STEREO SPEAKERS 10 + 10W AND UV2A LCD TECHNOLOGY
- ▶ BRIGHTNESS 700CD/M2
- ▶ LED, EDGE LIT
- ▶ 24 / 7 OPERATION
- ▶ HDMI AND DISPLAYPORT
- ▶ LANDSCAPE & PORTRAIT INSTALLATION SUPPORT

Built for 24/7 durability, and sized for flexible installation, the PN-U473 represents a dynamic new breed of indoor digital signage solutions. Thin and lightweight enough for easy installation in stores, offices, and public spaces, this monitor boast the outstanding image quality (700 cd/m<sup>2</sup>) needed to deliver truly compelling digital signage.

## DISPLAY MODULE DATA

- Panel Technology: **LCD UV2A**
- Native Resolution (Pixels): **1920 X 1080**
- Diagonal Size (inches / cm): **47/119.3**
- Aspect Ratio: **16:9**
- Backlight Technology: **EDGE LED**
- Brightness (cd/m<sup>2</sup>): **700**
- Contrast Ratio: **1300:1**
- Display Colours: **1.06b**
- Response Time (grey to grey avg) ms: **12**
- Viewing Angle (H/V)0 CR >10: **178/178**

## KEY SPECIFICATIONS

- 24/7 Operation Certified: ✓
- Built in Speakers (W): **10 X 10**
- Computer Input - Plug and Play: ✓
- Power Management: ✓
- Cabinet Colour: **BLACK**
- Fanless: ✓
- Multi-Screen Function - Videowall Mode (Enlarge Feature): ✓
- Daisychain (Mirror mode): ✓
- Hardware Diagnosis: ✓
- Monitor Control Software Support: ✓

## POWER SUPPLY AND OPERATING ENVIRONMENT

- Operating Voltage(ACV) / Frequency(Hz): **100 - 240/50 - 60**
- Power Consumption (W) (Operating MAX): **130**
- Power Consumption (W) (Standby): **0.5**
- Operating Temperature (oC): **0 - 40**
- Humidity (%): **20 - 80**
- Heat Dissipation (BTU/h) MAX: **443.58**

## WEIGHTS AND MEASURES

- Bezel Size (L/R) mm: **20**
- Bezel Size (U/L) mm: **19**
- Product Dimensions (W/H/D) mm: **1083 X 627 X 55**
- Product Weight Without Stand (Kg): **19**

## CONNECTIVITY (AUDIO/VIDEO) INPUT

- HDMI: **1**
- DVI-D: **1**
- DisplayPort: **1**
- Component: **1**
- Composite: **1**
- Audio 3.5mm Jack: **1**

## CONNECTIVITY (CONTROL/SERIAL DATA)

- RS232C IN: **1**
- RS232C OUT: **1**
- LAN Port: **1**

## SAFETY AND ENVIRONMENT (EUROPE)

- CE, CB Report: ✓
- Mercury Content (mg): **0**
- Presence of Lead (Accepted application of RoHS Directive): ✓

## INSTALLATION

- Landscape: ✓
- Portrait: ✓
- Mounting (VESA/Number of Points/Pitch mm): **4/400mm x 200mm**

## CONNECTIVITY (AUDIO/VIDEO) OUTPUT

- DVI-D: **1**
- Audio RCA R-L: **1**

[www.sharp-cee.com](http://www.sharp-cee.com)

**SHARP**

HEADQUARTERS SHARP CENTRAL & EASTERN EUROPE  
A-1020 VIENNA  
HANDELSKAI 342  
AUSTRIA  
PHONE: +43 1 72719-0  
FAX: +43 1 72719-289  
INTERNET: [WWW.SHARP-CEE.COM](http://WWW.SHARP-CEE.COM)