


# Sharp/ NEC PN-LA862



- Most natural writing experience – InGlass™ M5 premium touch system supports patented pressure sensitivity using passive pens as well as Windows Ink and palm rejection.
- Optional Windows based Intel SDM slot-in PC – driving unlimited versatility with powerful integrated computing for quick and easy access to your apps offering a secure and locked environment.
- Energy efficiency – built-in functionality including an ambient light sensor, human presence detection and eco modes help to reduce power consumption.
- Secure by design – the non-Android platform with additional security features meets the highest IT security standards.
- Increase your productivity – benefit from a free one-year license for FlatFrog Board for Rooms. FlatFrog Board whiteboard software makes hybrid work easy and productive for everyone

# Specifications

## DISPLAY MODULE DATA

<b>Panel Technology</b>	IPS with Direct LED backlights
<b>Native Resolution (Pixels)</b>	3840 x 2160
<b>Diagonal Size (inches / cm)</b>	86 / 217.4
<b>Aspect Ratio</b>	16:9
<b>Backlight Technology</b>	LED
<b>Brightness (cd/m<sup>2</sup>)</b>	450
<b>Contrast Ratio</b>	1200:1
<b>Response Time (grey to grey avg) ms</b>	8
<b>Viewing Angle (H/V) 0 CR &gt;10</b>	178 / 178
<b>Colour Depth [bit]</b>	1.073 (10bit)

## TOUCH INTERFACE SPECIFICATION

<b>Technology</b>	InGlass™ M5
<b>Number of Touch Points</b>	20
<b>Coating / Filter</b>	Anti-glare coating
<b>Screen Hardness (H)</b>	≥ 8
<b>Operating System Compatibility</b>	Native Multi-Touch: Windows 7, Windows 8, Windows 10, Linux, Android; Default Mouse: Windows XP, Windows Vista, Mac OS X
<b>Thickness [mm]</b>	3
<b>Haze Level [%]</b>	4 ~ 8
<b>Touch Method</b>	Finger; Gloves; Stylus (≥ 2 mm)
<b>Data Interface</b>	USB-HID
<b>Accuracy [mm]</b>	< 1
<b>Palm Rejection</b>	Yes
<b>Windows Ink</b>	Yes

## WEIGHTS AND MEASURES

<b>Bezel Size (L/R) mm</b>	4.8
<b>Bezel Size (U/L) mm</b>	4.8 / 32.3
<b>Product Dimensions (W/H/D) mm</b>	1,965.4 x 1,163.9 x 86.5
<b>Product Weight Without Stand (Kg)</b>	7.5

## CONNECTIVITY (AUDIO/VIDEO) INPUT

<b>HDMI</b>	2
<b>DisplayPort</b>	1

## CONNECTIVITY (CONTROL/SERIAL DATA)

<b>RS232C IN</b>	1
<b>LAN Port</b>	1
<b>USB</b>	4

## KEY SPECIFICATIONS

<b>Special Characteristics</b>	DICOM Simulation; HDMI ARC; Powered USB Port (5 W)
<b>24/7 Operation Certified</b>	•
<b>Local Dimming</b>	•
<b>Built in Speakers (W)</b>	10 W + 10 W

## POWER SUPPLY AND OPERATING ENVIRONMENT

<b>Operating Voltage(ACV) / Frequency(Hz)</b>	100-240; 50 / 60
<b>Power Consumption (W) (Operating MAX)</b>	275 shipping
<b>Operating Temperature (oC)</b>	+5 to +35
<b>Humidity (%)</b>	20 to 80
<b>Power Savings Mode [W]</b>	< 0.5 (ECO Standby); < 2 (Networked Standby)

## INSTALLATION

<b>Landscape</b>	•
<b>Portrait</b>	•
<b>Horizontal</b>	•
<b>Mounting (VESA/Number of Points/Pitch mm)</b>	4; 600 x 400

## CONNECTIVITY (AUDIO/VIDEO) OUTPUT

<b>DisplayPort</b>	1
<b>Audio/Headphone 3.5mm Jack</b>	1

## ACCESSORIES

<b>Shipping Contents</b>	1x 300 cm USB Cable; 2 x Passive Stylus; 2x AAA batteries; Blank Sticker; Bracket for Camera; Bracket for Mini PC; Cable Clamps; Display; Power Cable; Remote Control; Setup Manual
--------------------------	---

