

Monitory biurkowe

Sharp/ NEC MultiSync® E244FL



For driving down costs without compromising quality, the E-series prioritises user comfort and productivity making it an excellent solution for both the home office and for small to medium sized businesses for general office applications.

- Improve your Productivity – with embedded LAN and USB-C, this display serves as a docking hub in your Personal Workspace.
- Future-proof flexibility – wide connectivity provides high-level flexibility with LAN, DP, HDMI, USB Type C, USB A and audio output.
- Safeguarding user wellbeing – built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering.
- Ergonomic Office – full height adjustability (130 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, plus optional VESA mount plate for thin client devices.

Dane techniczne

Technologia panelu	VA TFT with W-LED backlight
Proporcje obrazu	16:9
Jasność (cd/m2)	250
Współczynnik kontrastu	1000:1
Wyświetlane kolory	16.77
Czas odpowiedzi (szary-do-szarego, średni) ms	6
Wymiary piksela (mm, w poziomie/w pionie)	0,275
Viewing Angle [°]	178
<hr/>	
Height adjustable stand [mm]	120
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	610
[AVSpecificationLandscapeDimensionsDepthMm]	283
[AVSpecificationLandscapeDimensionsHeightMinMm]	377
[AVSpecificationLandscapeDimensionsHeightMaxMm]	507
<hr/>	
Digital	DisplayPort, HDMI, USB Type C (60 W), USB ver. 3.1 (3 down / 1 up)
Output Control	1 x RJ45
<hr/>	
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	RoHS compliant, TCO 9.0
<hr/>	
System montażu (VESA/liczba punktów/rozstaw w mm)	100 x 100
Gniazdo zabezpieczające	True
<hr/>	
Przekątna (cale/cm)	24
Przekątna (cale/cm)	60
<hr/>	
Pobór mocy w trybie pracy (IEC62087:2012)	13 (Eco Mode 2), 19 (typ.)
Power Supply	Integrated Power Supply
<hr/>	
Special Characteristics	Low Blue Light, Local dimming

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable), Słuchawkowe
Safety & Ergonomics	EnergyStar 8.0, Flicker-free, Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE
<hr/>	
Gwarancja producenta (lata)	3 years warranty incl. backlight
<hr/>	
Temperatura podczas pracy (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
<hr/>	
Wymiary ramki (lewa/prawa) mm	1
Wymiary ramki (góra) mm	16
Wymiary ramki (dół) mm	16
<hr/>	
Masa produktu bez podstawy (kg)	5
Masa produktu z podstawą (kg)	8
<hr/>	
Wyposażenie	
Shipping Content	DisplayPort Cable, Power Cable, Setup Guide, USB-C Cable
<hr/>	
Horizontal Frequency [kHz]	31.5 - 81
Vertical Frequency [Hz]	50 - 75
<hr/>	
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
<hr/>	
Optimum Resolution	1920 x 1080 at 60 Hz

