


Computing Module Core i3 Processor

OPS Midrange (ADL).



Slot-in PC for all high-end signage applications.

The OPS Midrange (ADL) is the most versatile and intelligent slot-in PC on the market for flight and passenger information systems, retail and corporate signage, and interactive as well as kiosk applications.

Perfect for budget-conscious businesses and organisations, the OPS Midrange delivers the performance, reliability, needed to build tailored digital display solutions with confidence.

- **Best value for signage** - displaying digital signage content has never been more powerful in this product category, offering seamless playback of moving content and reliable operation in flight information display systems (FIDS) environments.
- **Long-term OS support** - with its Microsoft Windows 11 IoT pre-installed operating system and Long-term Servicing Channel (LTSC) you will receive software support for many years.
- **High usage flexibility** - thanks to wide connectivity such as 5 x USB, HDMI, DisplayPort, Gigabit Ethernet, RS-232 and Audio there's no need to add additional adapters or signal splitters.
- **Seamless and fully embedded** - the OPS form factor provides a compact and fully embedded solution ensuring that all connectors are integrated including Power, Video & Audio Signals and RS-232.
- **100% compatibility and enhanced feature-set** - in combination with supported Sharp large format and interactive displays.
- **High reliability** - ideally suited for 24/7 operation due to the use of highly reliable components.

Specifications

Order Codes

OPS Midrange (ADL-i3-d8/128/W11IoT B)	L50OPS-ADL-16583
--	------------------

PC Configuration

CPU	Intel® Core™ i3 1215U Processor; 6 Cores (2x Performance, 4x Efficient), maximum 4.4 GHz
RAM	8GB DDR4 dual channel
Mass Storage	128GB M.2 SSD (NVMe)
Graphics (board)	Intel® UHD Graphics for 12 th Gen Intel® Processors HW Codec: H.265/HEVC, VP8, VP9, MPEG2, JPEG, VC1, AVC, AV1 Decode; Direct3D 12.1 ; OpenGL 4.6 ; OpenCL 3.0
Operating System	Windows 11 IoT LTSC 2024

Connectivity

Interfaces Frontside	2x USB 3.1 Type A Gen 2x USB 2.0 Type A Gen 1x Type C USB 3.1 RJ45 10 / 100 / 1000 Mbps 1x DP-out (4K@60Hz) 1x HDMI out (4K@30Hz) 1x headphone
----------------------	--

Resolution

EDID/DDC support	Internal OPS interface HDMI up to 3840 x 2160 @ 60Hz* External HDMI interface up to 3840 x 2160 @ 30Hz
------------------	---

Electrical

Power Consumption [W]	Idle : 8.5 Max. turbo mode: 58
-----------------------	-----------------------------------

Environmental conditions

Operating Temperature [°C]	0 to 40
----------------------------	---------

Mechanical

Net Weight (kg)	0.8
Gross Weight (kg)	1.2
Size / Gross Dimensions (mm)	180 x 118 x 30 / 325 x 245 x 75

Additional features

Compatibility	All Sharp large format & interactive displays featuring an OPS slot*
Warranty	3 years warranty, additional services available



* Some NEC or Sharp Sharp displays might be limited
in resolution to a maximum of 4K@30Hz

For additional pictures and solutions overview,
visit www.sharppdisplays.eu for details.