

Projektor

# Sharp/ NEC P605UL Projektor



- No filter service required – a completely sealed optical laser LCD engine allows a filter-free design and brilliant colour brightness is maintained.
- Low Noise Level – with 19dB\*, the silent technology will not disturb your meeting.
- Future-proof input management – thanks to 4K@30 Hz input processing.
- No lamp replacement – up to 20,000 h maintenance free operation possible due to Laser Light Source.
- Risk Group 2 – because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.

# Dane techniczne

[AVSpecificationDataTerminalsIn]	HDMI, 15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr)
[AVSpecificationVideoColourStandards]	PAL 60, PAL N, PAL M, SECAM, NTSC (MHz) 3.58, NTSC (MHz) 4.44
<b>Wyposażenie</b>	
[AVSpecificationAccessories]	Pilot zdalnego sterowania, Instrukcja obsługi (CD-ROM), Kabel zasilający
[AVSpecificationPowerReqsVoltageMinV]	100
[AVSpecificationPowerReqsVoltageMaxV]	240

[AVSpecification3LcdPanel]	True
[AVSpecificationWeightKg]	9,7
[AVSpecificationLuminanceEcoModeAnsiLumen]	6000
[AVSpecificationLampLifetimeEcoModeH]	20000
[AVSpecificationFanEcoDb]	19
[AVSpecificationFanStandardDb]	25
[AVSpecificationChangeableLens]	True
[AVSpecificationZoomLensManual]	True
[AVSpecificationLensShiftH]	True
[AVSpecificationLensShiftV]	True
[AVSpecificationKeystoneManual]	True
[AVSpecificationAudioTerminals]	Mini Jack (3,5 mm) wej./wyj., Przez wejście HDMI
[AVSpecificationVideoTerminals]	HDMI
[AVSpecificationControlTerminals]	RS232C, LAN, USB-Host
Rozdzielczość znamionowa (piksele)	1920 x 1200 (WUXGA)
Współczynnik kontrastu	600000:1

