

# This is Why



- ▶ FANLESS AND NOISELESS MODULAR RESTAURANT AND BAR/PUB POS SYSTEM
- ▶ LARGE 38 CM TRUE FLAT COLOUR TOUCH SCREEN
- ▶ COMPACT AND POPULAR DESIGN
- ▶ HIGH VISIBLE ADJUSTABLE LEFT/RIGHT AND UP/DOWN LED BACKLIGHT LCD TOUCH SCREEN
- ▶ SUPERIOR EASY TO CLEAN AND HIGH IP RATING LCD FRONT PANEL
- ▶ INTEL CELERON BAY-TRAILJ1900 CPU
- ▶ SATA 2.5" SOLID STATE DISK 64GB TRANSCEND STANDARD
- ▶ WINDOWS POSREADY 7 OPERATING SYSTEM PRE-INSTALLED

The RZ-X735F tailor made POS terminal is especially suitable for the restaurant and bar/pub market environment. The true flat touch screen surface allows easy cleaning and avoids dust or crumbs in the LCD frame. A lot of opportunities are offered with the flexible PC-based POS terminal RZ-X735F as it allows to install specific application software dedicated to the market segments.

Apart from this, the RZ-X735F can be upgraded to an overall sophisticated system. This, due to the availability of several interfaces to connect different printers, a 26 cm colour LCD customer display, magnet card reader, security by applying the Dallas clerk key system etc.

Not only visually, but also from the daily work and efficiency standpoint the RZ-X735F is perfectly designed. The terminal can be placed directly on the checkout desk or installed at the wall. Thanks to its fanless technology the RZ-X735F reduces energy cost to a significant low level.

## DISPLAY

- ▶ Color touch (cm): **38 with LED Backlight/300cd/m2**
- ▶ TFT Color LCD display: ✓
- ▶ Size 1: **1.024 x 768 (XGA)**
- ▶ Size 2: **not supported**

## NETWORK

- ▶ Ethernet 10 / 100 / 1000 Mbps: ✓/✓/✗

## TECHNICAL SPECIFICATION

- ▶ Dimensions (W x D x H mm): **365 x 234 x 360**
- ▶ Weight (kg): **6.580kg**
- ▶ Power Consumption Operating (W): **less than 84W**
- ▶ EMV Class: **This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.**

## PC SYSTEM

- ▶ Operating system: **Windows POSReady 7**
- ▶ CPU: **Intel Celeron Bay-Trail J1900 2.0 GHz/Fanless**
- ▶ L2 Cache: **1MB**
- ▶ BIOS ROM (Flash ROM): **AMI BIOS**
- ▶ Standard RAM Memory: **2 GB**
- ▶ Maximum RAM Memory: **8 GB**
- ▶ Alternative Drive: **SATA 2.5" SSD 64GB**
- ▶ Video RAM: ✓
- ▶ Magnet card reader: **optional**
- ▶ LPT parallel port: **1**
- ▶ Customer display: **optional external 2 line customer or 29 cm LCD customer display**
- ▶ Drawer: **maximal 2**
- ▶ Handheld terminal: ✓

## I/O PORTS

- ▶ Serial RS232: **4**
- ▶ USB: **4**
- ▶ External Monitor (VGA interface): **1**
- ▶ Operator key lock: **optional Dallas key system**

[www.sharp-cee.com](http://www.sharp-cee.com)

**SHARP**

HEADQUARTERS SHARP CENTRAL & EASTERN EUROPE  
A-1020 VIENNA  
HANDELSKAI 342  
AUSTRIA  
PHONE: +43 1 72719-0  
FAX: +43 1 72719-289  
INTERNET: [WWW.SHARP-CEE.COM](http://WWW.SHARP-CEE.COM)