

Next generation A4 colour MFP

MX-C303W

Advanced A4 colour MFP that supports the office workflow environment



- Print, Copy, Scan, Fax, File
- Paper capacity: Std 300 Max 2700 sheets
- Single sign-on brings easy access to public cloud storage services
- Wireless LAN as standard and 2-line wired LAN support
- Pages per minute: 30 B/W, 30 Colour
- 7-inch colour LCD touchscreen with Easy UI mode
- Standard Reversing Single Pass Feeder (RSPF)
- Advanced data protection and access control with SSL validation and whitelisting

Specifications

GENERAL

Engine speed: A4 Colour (ppm)	30
Engine speed: A4 B/W (ppm)	30
Paper size: Min.-Max.	A6 - A4
Paper weight (g/m ²)	Min- Max 55 - 220
Paper capacity: Std. (sheets)	300
Paper capacity: Max. (sheets)	2700
Warm Up Time (sec.)	47
Memory general: Min./Max. (GB)	5
Harddisk	STD
Harddisk capacity (GB)	500
Duplex	STD
Power requirements - rated local AC voltage (Hz)	220 - 240V, 50 / 60Hz
Power consumption (kW)	1.84
Dimensions (mm)	491 x 568 x 516
Weight (kg)	35

DOCUMENT FEEDER

Original capacity (sheets)	50
----------------------------	----

DOCUMENT FILING

Document filing (Standard / Option)	Std
Document filing capacity: main & custom folders (pages)	20,000
Document filing capacity: quick file folder (pages)	10,000
Stored jobs	Copy, print, scan, fax transmission
Storage folders	Quick files folder, main folder, custom folder (1,000 folders)
Confidential storage	•

FAX

Fax (Standard / Option)	STD
Compression method	MH / MR / MMR / JBIG
Communication protocol	Super G3
Transmission time (sec.)	2
Modem speed (bps)	33.600 - 2.400
Transmission resolution (dpi)	STD 203.2 x 97.8, Ultra Fine 203.2 x 195.6, Super Fine 203.2 x 391, Ultra fine 406.4 x 391
Document size: Min.	A6
Document size: Max.	A4
Memory (MB)	1
Grey scale (levels)	256
Dial registration: rapid/speed dial	2000

WIRELESS LAN

Wireless LAN (Standard / Option)	STD
Compliant regulation	IEEE802.11n / g / b
Access mode	Infrastructure mode, Software AP mode
Security	WEP, WPA / WPA2-mixed PSK, WPA / WPA2-mixed EAP, WPA2 PSK, WPA2 EAP

COPIER

Original paper size: Max.	A4
First copy out time: Colour (sec.)	7.4
First copy out time: B/W (sec.)	6.3
E-sort Std.	•
Continuous copy (Max. copies)	9999
Scan resolution: B/W (dpi)	600 x 600, 600 x 400
Scan resolution: Colour (dpi)	600 x 600, 600 x 400
Print resolution (dpi)	600 x 600, 9,600 (equivalent) x 600
Gradation: B/W (equivalent levels)	256
Gradation: Colour (equivalent levels)	256
Zoom range (%)	25 - 400
Preset copy ratios	10 (5R / 5E)

SCANNER

Network Scanner (Standard / Option)	STD
Scan method Push scan and Pull scan	•
Push scan resolution (dpi)	100, 200, 300, 400, 600
Pull scan resolution (dpi)	75, 100, 150, 200, 300, 400, 600, 50 - 9600 via user setting
File formats	TIFF, PDF, PDF / A-1a, PDF / A-1b, encrypted PDF, XPS, compact PDF, JPEG, searchable PDF, OOXML (pptx, xlsx, docx) text (TXT [UTF-8]), rich text (RTF)
Scan destination: Desktop	•
Scan destination: FTP, Email	•
Scan destination: Network folder	•
Scan destination: USB memory	•

PRINTER

Resolution (dpi)	600 x 600, 9600 (equivalent) x 600
Network Printer (Standard / Option)	STD
Interface: Std./Opt.	STD: USB 2.0, 10Base-T / 100Base-TX / 1000Base-T
Supported OS: Std.	2008, 2008R2, 2012, 2012R2, 2016, Windows® 7, 8.1, 10, Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
Network protocols	TCP / IP
Printing protocols	LPR, Raw TCP (port 9100), POP3 (email printing) HTTP, IPP, FTP for downloading print files, IPP, SMB, WSD
PDL: Std./Opt.	STD: PCL 6, Genuine Adobe® PostScript®3
Available fonts	80 fonts for PCL, 139 fonts for Adobe PostScript 3

FINISHING

Output capacity: Max. (sheets)	150
--------------------------------	-----

TONER YIELD

Black (pages at 5% coverage)	6000
Cyan (pages at 5% coverage)	6000
Magenta (pages at 5% coverage)	6000
Yellow (pages at 5% coverage)	6000

