

Monitory biurkowe

# MULTISYNC E224F



- Cost and time saving operation – based on an intuitive OSD design making set-up simpler.
- Ergonomic Office – full height adjustability (120 mm), swivel, tilt and pivot functionality ensures perfect individual workspace set-up.
- Black and white colour versions – white is considered to reduce the impression of tunnel vision when placed in front of a white background such as office walls.
- Safeguarding user wellbeing – built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering, protecting users eyes.
- Best in form and function – future-ready design with 3-sided ultra-narrow bezel, available in black or white, complementing a fresh professional office interior.

# Dane techniczne

Technologia panelu	VA TFT with W-LED backlight
Proporcje obrazu	16:9
Jasność (cd/m2)	250
Współczynnik kontrastu	3000:1
Wymiary piksela (mm, w poziomie/w pionie)	0,249
Response Time (typ.) [ms]	6
Screen Tilt [°]	-5 - 25
Height adjustable stand [mm]	120
Screen Swivel [°]	-170 - 170
Screen Rotate [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	493
[AVSpecificationLandscapeDimensionsHeightMm]	483
[AVSpecificationLandscapeDimensionsDepthMm]	233
Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ecological Standards	RoHS compliant
Masa produktu bez podstawy (kg)	3
Masa produktu z podstawą (kg)	5
<b>Wyposażenie</b>	
Shipping Content	Power Cable, DisplayPort Cable, Setup Guide
Digital	DisplayPort, HDMI
Analog	D-sub 15 pin
Wymiary ramki (lewa/prawa) mm	3
Wymiary ramki (dół) mm	17
Power Supply	Integrated Power Supply

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Cable Management	True
Plug & Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable), Słuchawkowe
Safety & Ergonomics	ISO 9241-307 (pixel failure class I), Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE, EnergyStar 8.0, Flicker-free
Gwarancja producenta (lata)	3 years warranty incl. backlight
Temperatura podczas pracy (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
System montażu (VESA/liczba punktów/rozstaw w mm)	100 x 100
Gniazdo zabezpieczające	True
Przekątna (cale/cm)	22
Colours [Mio.]	16
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Vertical Frequency [Hz]	50 - 75
Optimum Resolution	1920 x 1080 at 60 Hz

