



- ▶ PRINT, COPY, SCAN, FAX, FILE
- ▶ PAGES PER MINUTE: 31 B/W 31 COLOUR
- ▶ PAPER CAPACITY: STD 600 MAX 2100 SHEETS
- ▶ A4 COLOUR MFP WITH SPACE-SAVING INNER FINISHER
- ▶ 7.0" TOUCH-SCREEN COLOUR LCD CONTROL PANEL WITH THUMBNAIL VIEWS
- ▶ HIGH-QUALITY 1200 X 1200 DPI PRINTING
- ▶ INDUSTRY-LEADING SECURITY SOLUTIONS FOR ULTIMATE DATA/DOCUMENT PROTECTION
- ▶ SHARP OSA 3.5 (OPEN SYSTEMS ARCHITECTURE) ALLOWS INTEGRATION WITH NETWORK APPLICATIONS AND MAKES THEM ACCESSIBLE FROM THE LCD CONTROL PANEL

The new MX-C312 A4 network colour MFP uses the same smart features and high performance technology that's built into our A3 MFPs, packed into a space-saving design that will fit right next to a filing cabinet. Everything about this MFP has been designed to increase productivity - the fast print speed of up to 31ppm even at 1200 x 1200 dpi, the fast scan speed of up to 33 opm, the powerful management functions and the remote front panel utility. The 7.0" colour touch-screen LCD display with customisable keys and thumbnail previews provides easy navigation in IT-oriented workflow intensive environments.

GENERAL

- ▶ Engine speed Colour ppm (A4): **31**
- ▶ Engine speed B/W ppm (A4): **31**
- ▶ Paper size: Min.-Max.: **A5 - A4**
- ▶ Paper weight (g/m2): **55 - 209**
- ▶ Paper capacity: Std (sheets): **600**
- ▶ Paper capacity: Max. (sheets): **2100**
- ▶ Warm Up Time (sec.): **90**
- ▶ Memory general min/max (MB): **512**
- ▶ Memory printer min/max (MB): **512 - 1536**
- ▶ Harddisk: **STD**
- ▶ Harddisk capacity (GB): **80**
- ▶ Duplex: **STD**
- ▶ Power requirements - rated local AC voltage (Hz): **220 - 240V, 50/60Hz**
- ▶ Power consumption (kW): **1,84**
- ▶ Dimensions (mm): **560 x 493 x 714**
- ▶ Weight (Kg): **46**

DOCUMENT FEEDER

- ▶ Original capacity (sheets): **50**

DOCUMENT FILING

- ▶ Document filing (Standard / Option): **STD**
- ▶ Document filing capacity- main and custom folders (pages): **5500**
- ▶ Document filing capacity - quick file folder (pages): **1700**
- ▶ Stored jobs: **Copy, print, direct print, scan, fax transmission**
- ▶ Storage folders: **Quick file folder, main folder, custom folder (max. 1000)**
- ▶ Confidential storage: **✓**

FAX

- ▶ Fax (Standard / Option): **OPT**
- ▶ Compression method: **MH/MR/MMR/JBIG**
- ▶ Communication protocol: **Super G3**
- ▶ Transmission time (sec): **2**
- ▶ Modem Speed (bps): **33.600 - 2.400**
- ▶ Transmission resolution: **STD 203,2 x 97,8 dpi/Extra Fine 406,4 x 391 dpi**
- ▶ Document Size (Min): **A5**
- ▶ Document Size (Max): **A4**
- ▶ Memory (MB): **8**
- ▶ Grey Scale levels: **256**
- ▶ Dial Registration; rapid/speed dial: **999**
- ▶ Broadcast Transmission (max. destinations): **500**

COPIER

- ▶ Original paper size (Max.): **A4**
- ▶ First copy out time Colour (sec.): **8,9**
- ▶ First copy out time B/W (sec.): **8,0**
- ▶ E-sort Std: **✓**
- ▶ Continuous copy (Max. copies): **999**
- ▶ Resolution Scan B/W (dpi): **600 x 600**
- ▶ Resolution Scan Colour (dpi): **600 x 600**
- ▶ Resolution Print (dpi): **1200 x 1200**
- ▶ Gradation (equivalent levels) - B/W: **2**
- ▶ Gradation (equivalent levels) - Colour: **256**
- ▶ Zoom range (%): **50 - 200**
- ▶ Preset copy ratios: **8**

SCANNER

- ▶ Network Scanner (Standard / Option): **STD**
- ▶ Scan method Push scan and Pull scan: **✓**
- ▶ Resolution push scan (dpi): **100,200, 300,400, 600**
- ▶ Resolution pull scan (dpi): **75,100, 150,200, 300,400, 600,50 to 9600**
- ▶ File formats: **XPS, TIFF, PDF, encrypted PDF, JPEG (colour only)**
- ▶ Scanner utilities: **Network Scan Tool, Sharpdesk, Sharp TWAIN**
- ▶ Scan destinations Desktop: **✓**
- ▶ Scan destination FTP, Email: **✓**
- ▶ Scan destination Network folder: **✓**
- ▶ Scan destination USB memory: **✓**

PRINTER

- ▶ Resolution (dpi): **1200 x 1200**
- ▶ Network Printer (Standard / Option): **STD**
- ▶ Interface Std/Opt: **STD USB 2.0,10Base-T/100Base-TX/1000Base-T**
- ▶ Supported OS Standard: **Windows XP, Windows Server 2003, Windows Vista, Windows Server 2008, Windows 7 Mac OS X 10.4 - 10.4.11,10.5 - 10.5.8,10.6 - 10.6.8,10.7 - 10.7.2**
- ▶ Network protocols: **TCP/IP (IPv4 and IPv6), IPX/SPX (NetWare), NetBEUI, EtherTalk (AppleTalk)**
- ▶ Printing protocols: **LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, Novell Printserver application with NDS and Bindery, FTP for downloading print files, EtherTalk printing, IPP**
- ▶ PDL Std/Opt: **STD PCL 5c/6, PS3 emulation, OPT XPS**
- ▶ Available fonts: **80 (PCL), 136 (PS3)**

FINISHING

- ▶ Output Capacity Max.: **280**
- ▶ Staple Capacity (sheets) Max.: **30**
- ▶ Off-set shifting: **OPT**

www.sharp-cee.com

SHARP
Be Original.

HEADQUARTERS SHARP CENTRAL & EASTERN EUROPE
A-1020 VIENNA
HANDELSKAI 342
AUSTRIA
PHONE: +43 1 72719-0
FAX: +43 1 72719-289
INTERNET: WWW.SHARP-CEE.COM