


# Sharp/ NEC MultiSync M861 AirServer



- Unhindered readability – no reflections from windows or other light sources means no disruption to the visibility of signage content or meeting room presentation.
- Secure remote management – control your devices remotely and securely using NEC NaviSet Administrator 2; proactively manage maintenance requirements saving time and resources.
- Future Ready Connectivity – featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.
- Enhanced imaging performance – advanced settings of visual parameters allow full control of brightness, colour, gamma and uniformity via the SpectraView Engine for precise, natural images.
- Mission-critical 24/7 ready operation – the selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

# Specifications

## DISPLAY MODULE DATA

<b>Panel Technology</b>	IPS with Direct LED backlights
<b>Native Resolution (Pixels)</b>	3840 x 2160
<b>Diagonal Size (inches / cm)</b>	86 / 217.4
<b>Aspect Ratio</b>	16:9
<b>Backlight Technology</b>	Direct LED
<b>Brightness (cd/m2)</b>	500
<b>Contrast Ratio</b>	≥ 8000:1
<b>Response Time (grey to grey avg) ms</b>	8
<b>Viewing Angle (H/V) 0 CR &gt;10</b>	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
<b>Colour Depth [bn]</b>	1.073 (10bit)
<b>Haze Level [%]</b>	Pro (28)

## POWER SUPPLY AND OPERATING ENVIRONMENT

<b>Operating Voltage(ACV) / Frequency(Hz)</b>	100-240 V AC; 50 / 60 Hz
<b>Power Consumption (W) (Operating MAX)</b>	320 shipping
<b>Operating Temperature (°C)</b>	0 to 40
<b>Storage Temperature [°C]</b>	-20 to 60
<b>Humidity (%)</b>	20 to 80
<b>Storage Humidity [%]</b>	10 to 80

## INSTALLATION

<b>Landscape</b>	•
<b>Portrait</b>	•
<b>Mounting (VESA/Number of Points/Pitch mm)</b>	4; 600 x 400 (FDMI)

## CONNECTIVITY (AUDIO/VIDEO) OUTPUT

<b>HDMI</b>	1
<b>DisplayPort</b>	1
<b>Audio/Headphone 3.5mm Jack</b>	1

## AIRSERVER EMBEDDED SCREEN MIRRORING SOLUTION

<b>Airplay</b>	Code and password; extend macOS display; iOS, iPadOS and macOS; screen mirroring and content sharing
<b>Google Cast</b>	Android, Chrome OS and Google Chrome; prompt security; screen mirroring and cast from apps with DRM
<b>Miracast</b>	Android and Windows; extend Windows 10 desktop; Miracast over infrastructure; screen mirroring; touchback and pen support
<b>Guest Connectivity</b>	2.4 and 5 GHz channel selection; access control (device only, Internet only or Internet / LAN; Wi-Fi Hotspot; WPA2 security
<b>Video Output</b>	Up to Full HD (1920 x 1080) at 60 fps
<b>No. of Connections</b>	1
<b>Networking</b>	1 x Gigabit LAN; 802.11 ac / b / g / n Wi-Fi; 802.1X security; IPv6 addresses; Proxy
<b>Automatic Updates</b>	Provides new features and security enhancements

## KEY SPECIFICATIONS

<b>Special Characteristics</b>	DICOM Simulation; HDMI ARC; Powered USB Port (10 W); Removable Logo
<b>24/7 Operation Certified</b>	•
<b>Limited Manufacturer's Warranty (yrs.)</b>	3
<b>Local Dimming</b>	•
<b>Built in Speakers (W)</b>	10W + 10W
<b>Power Management</b>	•
<b>Cabinet Colour</b>	Black
<b>Temperature Sensor</b>	•
<b>Brightness Sensor</b>	•

## WEIGHTS AND MEASURES

<b>Bezel Size (L/R) mm</b>	14.3
<b>Bezel Size (U/L) mm</b>	14.3 / 14.8
<b>Product Dimensions (W/H/D) mm</b>	1,927.6 x 1,099.1 x 83.2
<b>Shipping Carton Dimensions (W/H/D) mm</b>	2,090 x 1,225 x 225
<b>Product Weight Without Stand (Kg)</b>	47
<b>Shipping Weight (Kg)</b>	65.1

## CONNECTIVITY (AUDIO/VIDEO) INPUT

<b>HDMI</b>	2
<b>DisplayPort</b>	2
<b>Audio 3.5mm Jack</b>	1

## CONNECTIVITY (CONTROL/SERIAL DATA)

<b>RS232C IN</b>	1
<b>LAN Port</b>	1
<b>USB</b>	3

## ACCESSORIES

<b>Shipping Content</b>	2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual
<b>Remote Control Transmitter</b>	Yes
<b>Power Cord</b>	Yes
<b>Mounting Bracket</b>	Optional
<b>Tabletop Stand</b>	Optional
<b>Battery</b>	Yes

