



- ▶ 90" (228,7 CM) DISPLAY FOR PROFESSIONAL 24/7 SIGNAGE
- ▶ 1920 X 1080 PIXELS WITH 700CD/M2
- ▶ SLIM BEZEL DESIGN WITH BUILT-IN STEREO SPEAKERS 10 + 10W
- ▶ CONTRAST 4000:1
- ▶ LED, FULL ARRAY
- ▶ 24 / 7 OPERATION
- ▶ LANDSCAPE & PORTRAIT INSTALLATION SUPPORT
- ▶ SHARP UV2A DISPLAY TECHNOLOGY

The Sharp PN-R monitor series have set a new benchmark for mission-critical reliability and flexible extension. These displays have been specially designed for a range of demanding and high brightness 700cd/m² applications including command and control rooms, 24/7 retail signage, transport signage, way-finding, hospitality, reception areas, lobbies and other corporate and public spaces. With an elegant, slim and discreet cabinet design the latest generation of PN-R Series offers powerful imaging, ease of use and peace-of-mind.

The amazingly large PN-R 90" (228.7 cm) is designed for demanding high brightness 24/7 display applications. As an easy-to-use and highly reliable solution with outstanding high-brightness image and sound quality, the PN-R903A sets the ultimate standard for reliable, robust, plug-and-go display signage used anytime and anywhere.

With state-of-the-art high-brightness LED backlight technology, which allows for a new level of slim bezels and shallow cabinet depth, Sharp's 90" PN-R903A display is an attractive and elegant addition to any demanding signage application. With unparalleled reliability, superb durability and straight-forward operation, the monitor can be installed in either portrait or landscape mode.

The in-built loop-through capability via the DisplayPort and DVI-D video connections allows easy mirrored display content. Just another reason why Sharp's LCD monitors can be employed to broaden your business potential.

DISPLAY MODULE DATA

- Panel Technology: **LCD UV2A RGB**
- Native Resolution (Pixels): **1920 x 1080**
- Diagonal Size (inches / cm): **90/228.7**
- Aspect Ratio: **16 : 9**
- Backlight Technology: **LED Full Array**
- Brightness (cd/m²): **700**
- Contrast Ratio: **4000:1**
- Display Colours: **1.06b**
- Response Time (grey to grey avg) ms: **6**
- Viewing Angle (H/V)0 CR >10: **176/176**

KEY SPECIFICATIONS

- 24/7 Operation Certified: **✓**
- Built in Speakers (W): **10 x 10**
- Computer Input - Plug and Play: **✓**
- Power Management: **✓**
- Cabinet Colour: **BLACK**
- Fanless: **✓**
- Multi-Screen Function - Videowall Mode (Enlarge Feature): **✓**
- Daisychain (Mirror mode): **✓**
- Hardware Diagnosis: **✓**
- Monitor Control Software Support: **✓**

POWER SUPPLY AND OPERATING ENVIRONMENT

- Operating Voltage(ACV) / Frequency(Hz): **100-240/50-60**
- Power Consumption (W) (Operating MAX): **660**
- Operating Temperature (oC): **0 to 40**
- Humidity (%): **20 to 80**
- Heat Dissipation (BTU/h) MAX: **2253.52**

WEIGHTS AND MEASURES

- Bezel Size (L/R) mm: **35**
- Bezel Size (U/L) mm: **27**
- Product Dimensions (W/H/D) mm: **2,055 x 1,197 x 122**
- Product Weight Without Stand (Kg): **75 kg**

CONNECTIVITY (AUDIO/VIDEO) INPUT

- HDMI: **2**
- DVI-I: **1**
- DisplayPort: **1**
- VGA: **1**
- Component: **1**
- Composite: **1**
- Audio 3.5mm Jack: **2**

CONNECTIVITY (CONTROL/SERIAL DATA)

- RS232C IN: **1**
- RS232C OUT: **1**
- LAN Port: **1**

SAFETY AND ENVIRONMENT (EUROPE)

- CE, CB Report: **✓**
- Mercury Content (mg): **0**
- Presence of Lead (Accepted application of RoHS Directive): **✓**

INSTALLATION

- Landscape: **✓**
- Portrait: **✓**
- Mounting (VESA/Number of Points/Pitch mm): **4/600mm x 400mm or 4/600mm x 600mm**

CONNECTIVITY (AUDIO/VIDEO) OUTPUT

- DVI-D: **1**
- DisplayPort: **1**
- Audio/Headphone 3.5mm Jack: **1**

www.sharp-cee.com

SHARP

Be Original.

HEADQUARTERS SHARP CENTRAL & EASTERN EUROPE
A-1020 Vienna
Handelskai 342
Austria
Phone: +43 1 72719-0
Fax: +43 1 72719-289
Internet: www.sharp-cee.com