

This is Why



- ▶ FANLESS AND NOISELESS MODULAR RETAIL AND FAST FOOD POS SYSTEM
- ▶ LARGE 38 CM TRUE FLAT COLOUR TOUCH SCREEN
- ▶ COMPACT AND POPULAR DESIGN
- ▶ HIGH VISIBLE ADJUSTABLE LEFT/RIGHT AND UP/DOWN LED BACKLIGHT LCD TOUCH SCREEN
- ▶ SUPERIOR EASY TO CLEAN AND HIGH IP RATING LCD FRONT PANEL
- ▶ 10/100/1000 BASE ETHERNET CONNECTION
- ▶ HARD DISK SUPPORTS SMART (SELF MONITORING/ANALYSIS AND REPORTING TECHNOLOGY)
- ▶ WEPOS READY 2009 PRE-INSTALLED

Especially small and mid size companies must be highly flexible to survive in their daily business against larger companies. With the need of being active in the retail and fast food market, the flexible PC-based POS terminal RZ-X750FV4 offers a lot of additional opportunities, as it allows to install specific application software dedicated to the market segments. Apart from this, the RZ-X750FV4 can be upgraded to an overall sophisticated system. This, due to the availability of several interfaces to connect different printers, a 26,4 cm LCD customer display, magnet card reader etc. Not only visually, but also from the daily work and efficiency standpoint the RZ-X750FV4 is perfectly designed. The terminal can be placed directly on the checkout desk or installed at the wall. Thanks to its fanless technology the RZ-X750FV4 reduces energy cost to a significant low level.

DISPLAY

- Color touch (cm): **38**
- TFT Color LCD display: ✓
- Size (dots) adjustable: ✓
- Size 1: **1.024 x 768 (XGA)**
- Size 2: **Not supported**

NETWORK

- Ethernet 10 / 100 / 1000 Mbps: ✓/✓/✗

TECHNICAL SPECIFICATION

- Dimensions (W x D x H mm): **365 x 234 x 360**
- Weight (kg): **6.5**
- Power Consumption Operating (W): **max. 180 (without peripherals)**
- EMV Class: **This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.**

PC SYSTEM

- Operating system: **WEPOS Ready 2009**
- CPU: **Intel ATOM 1.8 GHz (D525)**
- L1 Cache: **L1 D-Cache: 48KB (24KB X 2)L1 I-Cache: 64KB (32KB X 2)**
- L2 Cache: **1MB (512KB X 2)**
- BIOS ROM (Flash ROM): **AMI SHARP**
- Standard RAM Memory: **2 GB**
- Maximum RAM Memory: **4 GB**
- Hard Disk Drive: **320 GB**
- Video RAM: ✓
- Magnet card reader: **optional**
- LPT parallel port: **1**
- Customer display: **Optional external 2 line customer or 29 cm LCD customer display**
- Drawer: **maximal 2**
- Handheld terminal: ✓

I/O PORTS

- Seriel RS232: **4**
- USB: **5/1 powered USB**
- External Monitor (VGA interface): **1**

www.sharp-cee.com

SHARP

HEADQUARTERS SHARP CENTRAL & EASTERN EUROPE
A-1020 VIENNA
HANDELSKAI 342
AUSTRIA
PHONE: +43 1 72719-0
FAX: +43 1 72719-289
INTERNET: WWW.SHARP-CEE.COM