

Monitory biurkowe

NEC MULTISYNC EA272F



NEC MultiSync

- In-demand display size – the popular 27.0" display with Full HD resolution is the perfect size for busy office workspaces.
- Clutter-free workspace – Powerful 65W USB Type-C connectivity manages video, audio, power and USB via a single cable.
- Future-proof flexibility – wide connectivity provides high-level flexibility with DP, HDMI, USB Type C, USB A and audio output.
- Easy multi-screen set-up – Daisy-chain multiple display configurations through DisplayPort-out, no additional cables needed.
- Maximum attention to health and well-being – with outstanding ergonomic height adjustment from 0 to 150 mm; built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor.

Dane techniczne

Technologia panelu	AH-IPS LCD with LED backlight
Proporcje obrazu	16:9
Jasność (cd/m2)	250
Współczynnik kontrastu	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
Wyswietlane kolory	16.78
Czas odpowiedzi (szary-do-szarego, średni) ms	6
Wymiary piksela (mm, w poziomie/w pionie)	0,311

Energy Efficiency	Ambient light sensor, Auto brightness, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 15 kWh/1000 h, Energy efficiency class: D, Human sensor, LED backlight technology
-------------------	--

Ecological Standards	Efficient mechanical design for minimised packaging, Minimal use of harmful material
----------------------	--

Ecological Materials	ErP compliant, WEEE
----------------------	---------------------

Height adjustable stand [mm]	150
Screen Rotate [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	360
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	610
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	628
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	377
[AVSpecificationLandscapeDimensionsHeightMaxMm]	527

Optimum Resolution	1920 x 1080 at 60 Hz
Supported Resolution	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 720 x 400 (70 Hz), 800 x 600

Wyposażenie

Shipping Content	Control Sync cable, DisplayPort Cable, Monitor, Power Cable, Setup Manual, Setup Guide, USB cable, USB-C Cable
------------------	--

Digital	DisplayPort, DisplayPort out, HDMI, USB ver. 3.1 (3 down / 1 up), USB Type C
---------	--

Analog	VGA
--------	-----

Wymiary ramki (lewa/prawa) mm	1
Wymiary ramki (górn) mm	1
Wymiary ramki (dół) mm	16

Horizontal Frequency [kHz]	31.5 - 83
Vertical Frequency [Hz]	55 - 75

Colour Versions	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
-----------------	--

Cable Management	True
Plug & Play	DDC2B/2Bi, EDID Standard, VESA DDC/CI

Audio	Sluchawkowe, Integrated Speakers (1 W + 1 W)
-------	--

Adjust Functions	Audio Volume / Lock-Out, Auto Adjust, Jasność, Colour Temperature Control, Kontrastu, Control Sync, DV Mode, EcoMode, Factory Preset, Fine Adjust (analog), Human Sensing, Intelligent Power Management, Language Select, Monitor Information, NTA (Non-Touch-Auto-Adjustment), On-Screen-Display (OSD) lock-out, One Touch Recovery, Power-Off Timer, sRGB CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class 2), ISO 9241-307 (pixel failure class 1), Low Blue Light, PSB, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA, TCO Edge 2
------------------	---

Safety & Ergonomics	
Gwarancja producenta (lata)	3 years warranty incl. backlight, Optional 4th to 5th year warranty extension

Special Characteristics	DDC/CI compatible, RGB Support, Frame Comp, PLink Support, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Touch Sensor Keys, USB ver. 3.0 (3 down / 1 up)
-------------------------	--

Temperatura podczas pracy (oC)	5 - 35
Storage Temperature [°C]	-10 - 60
Storage Humidity [%]	10
Storage Humidity [%]	85

Przekątna (cale/cm)	27
Przekątna (cale/cm)	69
Colour Gamuts	102 % sRGB, 75.5% AdobeRGB, 72% NTSC

Pobór mocy w trybie pracy (IEC62087:2012)	15 (Eco Mode 2), 21 (typ.)
Power Supply	0.85 A/0.45 A, 100-240 V, Integrated Power Supply

System montażu (VESA/liczba punktów/rozstaw w mm)	100 x 100
Gniazdo zabezpieczające	True

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: NEC MultiSync EA272F, 22/6/2026