

This is Why



- ▶ 1-CHIP DLP (TI) WXGA (1280 X 800 PIXEL)
- ▶ HIGH BRIGHTNESS (4500 AL)
- ▶ H&V LENS-SHIFT-SYSTEM
- ▶ CONTROL INPUTS RS232 AND LAN
- ▶ LENS THROW RATIO 1,5 - 3
- ▶ 3D READY SYSTEM (DLP-LINK)
- ▶ 3D KEYSTONE
- ▶ OPTION AN-SV100T MOTOR SYSTEM (360°)

The XG-SV100W (WXGA) is Sharp's premier installation/integration projector designed for use in almost any high-end application – including conference facilities, lecture halls, rental, staging, house of worship and Command and Control.

PANEL RESOLUTION

- ▶ Chip panel size: **DMD/0,7"**
- ▶ 1-Chip DLP(TI) / 3-Chip DLP(TI) / 3-LCD-Panel: ✓/✗/✗
- ▶ Native Resolution: **WXGA 1280 x 800**
- ▶ UXGA 1.600 x 1.200: ✓
- ▶ SXGA+ 1.400x1.050: ✓
- ▶ SXGA 1.280x1.024: ✓
- ▶ WXGA 1.280 x 800 / 1.360x 768 / 1.366 x 768: ✓/✓/✓
- ▶ XGA 1.024 x 768: ✓
- ▶ SVGA 800 x 600: ✓
- ▶ Mac Compatible: ✓

DATA TERMINALS

- ▶ HDMI: ✓
- ▶ 15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr): ✓

CONTROL TERMINALS

- ▶ RS232C (Sub-D): ✓
- ▶ LAN: ✓
- ▶ USB-Host: ✓

COLOUR STANDARDS

- ▶ PAL 60/N/M: ✓/✓/✓
- ▶ SECAM: ✓
- ▶ NTSC (MHz) 3.58/ 4.43: ✓/✓
- ▶ Video Resolution, DTV-Lines / TV-Lines: **720**
- ▶ DTV 480i/480p/540p: ✓/✓/✓
- ▶ 576i/576p: ✓/✓
- ▶ 720p/1.035i: ✓/✗
- ▶ 1.080i/1.080p: ✓/✓
- ▶ 1.080/24p: ✓

AUDIO DATA

- ▶ Audio-Monitor (stereo/mono): ✗/✓
- ▶ Output Power (W), RMS: **10**

OTHERS

- ▶ Special Features: **Option AN-SV100T 360° Motor**
- ▶ Class A: **This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.**
- ▶ Power supply (V) / power consumption, standard (W) / power consumption, ECO (W) / stand-by (W): **100 - 240/0,7/309**
- ▶ Heat Dissipation (BTU / h): ECO-Mode / Standard: **1054**
- ▶ Dimensions in mm (W x H x D): **405 x 134,5 x 406,5**
- ▶ Weight (kg): **7,5**
- ▶ EAN-code: **4974019703978**

PC-INPUT

- ▶ H-Frequency (kHz): **15 - 110 KHz**
- ▶ V-Frequency (Hz): **45 - 85 Hz**
- ▶ Pixel Clock (MHz): **165 MHz**

VIDEO TERMINALS

- ▶ Composite (RCA/BNC): ✓
- ▶ S-Video (Y/C): ✓
- ▶ Component (RCA/BNC): ✓
- ▶ HDMI: ✓
- ▶ HDCP Compatible: ✓

AUDIO TERMINALS

- ▶ RCA-Stereo Terminal In/Out: ✓
- ▶ Via HDMI-Terminal: ✓

PICTURE DATA

- ▶ Luminance ECO-mode (ANSI Lumen) / Standard (ANSI Lumen): **4500**
- ▶ Contrast: **2000**
- ▶ Projection lamp (W) / Lamp lifetime ECO-Mode (h) / Lamplife Standard (h): **400/2500/2000**
- ▶ Fan: **34 dB ECO/39 dB Standard**
- ▶ Lens built-In / Changeable Lens: ✓/✗
- ▶ Zoom-Lens (Manual/ Motorized): ✗/✓
- ▶ Zoom-Lens (Focal length, mm): **21,2 - 42**
- ▶ Luminous Intensity (F): **2,5 - 3,7**
- ▶ Lens Shift (H/V): ✓/✓
- ▶ Lens Ratio (Width to Distance): **1,5 - 3**
- ▶ Keystone (3D/digital): ✓/✓

ACCESSORIES

- ▶ Remote Control / Owners Manual (CD-ROM): ✓/✓
- ▶ Power Cable / PC Cable: ✓/✓

www.sharp-cee.com

SHARP

HEADQUARTERS SHARP CENTRAL & EASTERN EUROPE
A-1020 VIENNA
HANDELSKAI 342
AUSTRIA
PHONE: +43 1 72719-0
FAX: +43 1 72719-289
INTERNET: WWW.SHARP-CEE.COM